



FIRE EXTINGUISHER
HEAT ACTIVATED DISCHARGE
USCG AND FM APPROVED

AIR FLOW
MONITOR(OPT)

SER. # & I.D. PLATE

LIGHT SWITCH

BLOWER SWITCH
(OPT)

SERVICE
FIXTURES
(RT AND/OR LFT)
(OPT)

DUPLEX
RECEPT.
(RT AND/OR LFT)
(OPT)

WORKSURFACE
(OPT)

MODEL 12240
(WITH OPTIONAL BASE CABINET
AND WORKSURFACE)

MODEL 12250
(WITH OPTIONAL TABLE
AND WORKSURFACE)

MODEL 12260
(WITH OPTIONAL ACID/BASE CABINETS
AND WORKSURFACE)

MODEL 12280
(WITH OPTIONAL BASE CABINETS
AND WORKSURFACE)

SECTION A-A

OPTIONAL EQUIPMENT AND SERVICES

1. PLUMBING SERVICE
2. ELECTRICAL SERVICES
3. EXHAUST SYSTEMS
4. FIRE EXTINGUISHER
5. AIR FLOW ALARM
6. VERTICAL RISING SASH
7. COMBINATION SASH

NOTE:
ALL ELECTRICAL COMPONENTS
UL AND CSA LISTED.

DUALFAM122X0-SV

UNIFLOW DUAL ENTRY FUME HOOD SERIES 02 VAPOR PROOF LIGHT				
SCALE:	APPROVED BY:	DATE:	REVISION:	DATE:
DRAWN BY: TLF	REP:	QUOTE No:	XXXX XXXX	XX/XX/XX
DATE: 09/08/03	PROJECT MGR:	DATE:		
HEMCO Corporation		© PLANS AND DRAWINGS ARE COPYRIGHTED		DWG. NO. M01-3291
111 POWELL RD INDEPENDENCE, MO. 64056 PH:816-796-2900 FAX:816-796-3333		BY _____ DATE _____	SHEET. 1 OF 1	