



the standard in safety

Underwriters  
Laboratories

File MH47367

Vol 1

Issued: 2010-08-16  
Revised: 2010-08-16

FOLLOW-UP SERVICE PROCEDURE  
(TYPE R)

LABORATORY HOODS AND CABINETS  
(OGOY)

Manufacturer: HEMCO CORP  
(100082-740) 711 S POWELL RD  
INDEPENDENCE MO 64056

Applicant: SAME AS MANUFACTURER  
(100082-740)

Classified Company: SAME AS MANUFACTURER  
(100082-740)

This Procedure authorizes the above manufacturer to use the marking specified by Underwriters Laboratories Inc. (UL), or any authorized licensee of UL, only on products covered by this Procedure, in accordance with the applicable UL Services Agreement.

The prescribed Mark or Marking shall be used only at the above manufacturing location on such products which comply with this Procedure and any other applicable requirements.

The Procedure contains information for the use of the above named Manufacturer and representatives of Underwriters Laboratories Inc. and is not to be used for any other purpose. It is lent to the Manufacturer with the understanding that it is not to be copied, either wholly or in part, and that it will be returned to Underwriters Laboratories Inc. (UL) or any authorized licensee of UL, upon request.

This PROCEDURE, and any subsequent revision, is the property of Underwriters Laboratories Inc. (UL) and the authorized licensee of UL and is not transferable.

Underwriters Laboratories Inc.

Stephen Hewson  
Senior Vice President  
Global Follow-Up Service Operations

William R. Carney  
Director  
North American Certification Program

(FILE IMMEDIATELY AFTER AUTHORIZATION PAGE)

CLASSIFICATION MARK

COMPOSITION AND ELEMENT:

The Classification Mark shall consist of the following and shall appear on the product container packaging or as indicated in the Guide Information for the CCN.

(APPROPRIATE PRODUCT IDENTITY)  
IN ACCORDANCE WITH UL 1805 or  
AS TO FIRE, ELECTRICAL AND MECHANICAL  
HAZARDS ONLY  
3XK8

MARKING:

The following symbol must be located adjacent to or in close proximity to the regular Classification Mark as shown above.



The minimum height of the registered trademark symbol ® shall be 3/64 of an inch. When the overall diameter of the UL Mark is less than 3/8 of an inch, the trademark symbol may be omitted if it is not legible to the naked eye.

PROCUREMENT:

The manufacturer may reproduce the mark or obtain it from a UL authorized supplier.